





SPOTTED GUM

ORIGIN	New South Wales and Queensland
SPECIES TYPE	Hardwood
SUSTAINABILITY	Available in PEFC/AFS with a Chain of Custody for Green Star points. On request only.
AVAILABILITY	Readily available
DURABILITY	Class 1 – greater than 40 years
HARDNESS	Janka 11kN
DENSITY (DRY)	990kg/m ³
MOVEMENT	Medium tangential 6.1% (shrinkage across the board width)
LYCTID SUSCEPTIBILITY	Susceptible
TERMITE RESISTANCE	Resistant
FIRE	Satisfies BAL 12.5, 19 and 29 under AS3959-2009. Satisfies BCA C1.10a Group 3
LENGTHS	Average length 2.4m (this can vary depending on availability)
TYPICAL APPLICATIONS	Internal cladding and battens External cladding and battens

BOTANICAL NAME: EUCALYPTUS MACULATA

Spotted Gum has a wide range of colours depending on the location of the source forest. Ranging from light brown through definite browns to deep red-brown hues. It can also have patches of white to light brown colours running through it up to 50mm wide. Spotted Gum is a moderately coarse and uneven textured wood with some timbers having the additional feature of a wavy grain, giving rise to an attractive fiddleback figure.

TYPICAL CHARACTERISTICS



January 2016 | 01290116



1800 008 828
sculptform.com.au | support@sculptform.com.au

REFERENCES: Wood Solutions (www.woodsolutions.com.au); Australian Standards AS5604-2005; Wood in Australia by Keith R. Bootle 2002 ISBN 0 07 451047 9.; Australian Standards AS 3959-2009

NOTE: To maintain currency, this document is periodically reviewed, and new editions are published. Between editions, amendments may be issued, so its important that readers assure themselves they are using a current document. We welcome suggestions for improvement, and encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email support@sculptform.com.au or phone 1800 008 828.

Available in PEFC/
Responsible Wood with
a Chain of Custody for
Green Star points. On
request only.

